



Multigrey

RIGA® Heksa Plus

RIGA® Tex

Surface

Decorative and practical

Colour - a light & dark grey mix

Easy care - virtually dust free

Light wear and scratches are barely visible

Highly resistant to mechanical damages

Repellent to water, release oils, diluted acids, alkalis and solvents

Melamine resin based film with weight alternatives 190 and 358 g/m²

Applications

Flooring, transport industry, storage and factory floors, stages, storage shelves, loading platforms, pier surfaces, scaffoldings, ship decks, shop fitting and flight cases.

In general - surfaces where high wear resistance is required.

Reaction to fire classification

B_{f1}-s1 (EN 13501)

Taber Values

Multigrey film	Wear resistance class
RIGA® Tex, 190 g/m ²	Class 6 > 800 revolutions
RIGA® Tex, RIGA® Heksa Plus, 358 g/m ²	Class 7 > 1000 revolutions

Standard sizes

1220 mm x 2440 / 3050 mm

1250 mm x 2500 / 3000 mm

1500 mm x 2500 / 3000 mm

1525 mm x 2440 / 3050 mm

2150 mm x 3050 / 3340 / 3850 mm

Cut-to-size & Machining upon customer requirements

Standard thicknesses

9, 12, 15, 18, 21, 24, 27, 30, 35, 40 mm

